

Manual Microcement fixprimer

Microcement fixprimer by betonlook.nl is a white, water-based primer specially developed for furniture, window sills and other smooth substrates. The primer creates an even white base and reduces or eliminates the visibility of wood grain and wood-based materials. This results in a neutral and stable surface for the application of Beton Ciré.

Advantages of Microcement fixprimer

Ease of use

The fixprimer is easy to apply with a microfibre roller for larger surfaces and a brush for edges and smaller areas. This makes it straightforward to use, regardless of the size or shape of the surface.

Stabilises the substrate

The fixprimer seals slightly powdery and absorbent substrates and prevents uneven absorption of the finishing product. This creates a calm, even base and a more consistent final result.

Improved adhesion

Using the fixprimer creates a strong and uniform bond between the substrate and the finishing product. This reduces the risk of peeling, staining and colour differences.

Application of Microcement fixprimer

Coverage

Mit 1 kg fixprimer können ca. 4–5 m² behandelt werden, abhängig von der Saugfähigkeit des Untergrunds. Bei Bedarf kann der fixprimer mit bis zu 15 % Wasser verdünnt werden, beispielsweise bei stark saugenden Untergründen.

Substrate preparation

Ensure the substrate is clean, dry and dust-free before starting. The surface must be solid, stable and non-powdery. Carefully remove any loose particles and dirt beforehand.

On wooden substrates with an existing lacquer layer, the surface must be fully sanded using 120-grit sandpaper to ensure proper adhesion.

Apply the primer evenly with a microfibre roller or brush and avoid visible overlaps.

Drying time

Allow the fixprimer to dry for at least 6–12 hours before applying the subsequent product. The exact drying time depends on temperature, ventilation and substrate conditions.

Storage

Store in a cool and dry place and protect from frost. In unopened packaging, the fixprimer has a shelf life of approximately 12 months at temperatures between 10°C and 30°C. Keep out of reach of children.

Tips

- Stir or shake well before use.
- Always apply a thin and even coat.