

# Natural paint sealer manual

---

Natural paint sealer is an environmentally friendly, semi-transparent coating made from eggshells that sustainably protects paint. It effectively repels dirt and dust, extending the lifespan of paint. However, due to its natural composition, it is not suitable for stubborn stains or chemical substances.

## Preparation of a smooth surface

### Painted surface

Apply Natural paint sealer only after the underlying paint layer has dried for 24 hours. Apply a single layer of Natural paint sealer over the paint with texture.

## Applying Natural paint sealer

### Step 1

Mix the Natural paint sealer. Use a ratio of 500ml of water per 50 grams of Natural paint sealer. Add the water gradually to prevent clumps. Mix the mixture thoroughly using a whisk. Want to be sure that the mixture is free of lumps? Strain the mixed Natural paint sealer through a sieve. Let the mixture rest for 15 minutes.

### Step 2

The Natural paint sealer is now ready to be applied.

### Step 3

Apply the Natural paint sealer using the Special effect brush from betonlook.nl. The Natural paint sealer will be dry after 24 hours and requires five days to cure fully.

## Mixing ratios for Natural paint sealer

### Mixing ratio for Natural paint sealer 5 m<sup>2</sup>

You ordered 50g of Natural paint sealer for 5m<sup>2</sup> and received 50g of Natural paint sealer. Mix 50g of Natural paint sealer with 500ml of water. Let it rest for 15 minutes before applying.

### Mixing ratio for Natural paint sealer 10 m<sup>2</sup>

You ordered Natural paint sealer for 10m<sup>2</sup> and received 100g of Natural paint sealer. Mix 100g of Natural paint sealer with 1 litre of water. Let it rest for 15 minutes before applying.

### Mixing ratio for Natural paint sealer 50 m<sup>2</sup>

You have ordered Natural paint sealer for 50m<sup>2</sup> and received 500g of Natural paint sealer. Mix 500g of Natural paint sealer with 5 litres of water. Let it rest for 15 minutes before applying.

## Tips

- Apply a maximum of one layer of Natural paint sealer on the wall.
- Natural paint sealer is not resistant to grease splashes, so we strongly advise against using it in the kitchen.
- Natural paint sealer seals off the breathable properties of our paint types. Therefore, we do not recommend using it in spaces where our paint needs to breathe, such as damp areas like bathrooms and kitchens.
- Wait 5 days for the Natural paint sealer to cure fully. Clean the surface only with a slightly damp cloth, which is not entirely waterproof. Chemical cleaning agents are strictly discouraged, as they may damage the protective layer.